Commercial & Mil-Spec Aircaft Cable- Stainless

Diameter (inches)	Diameter (Metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/ 1000 ft.	Code
1/32	0.80	7x7	115	1.6	С
3/64	1.20	7x7	270	4.2	C & M
1/16	1.60	7x7	480	7.5	C & M
5/64	2.00	7x7	650	11	С
3/32	2.40	7x7	920	16	C & M
1/8	3.20	7x7	1,700	28	С
5/32	4.00	7x7	2,400	43	С
3/16	4.80	7x7	3,700	62	С
7/32	5.60	7x7	4,800	83	С
1/4	6.40	7x7	6,100	106	С
5/16	7.90	7x7	9,000	167	С
3/8	9.50	7x7	12,000	236	С

7X19 Preformed T302/04 Stainless Steel Wire Rope Flexible							
Diameter (inches)	Diameter (Metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/ 1000 ft.	Code		
1/16	1.60	7x19	480	7.5	C & M		
3/32	2.40	7x19	920	16	C & M		
1/8	3.20	7x19	1,760	29	C & M		
5/32	4.00	7x19	2,400	45	C & M		
3/16	4.80	7x19	3,700	65	C & M		
7/32	5.60	7x19	5,000	86	C & M		
1/4	6.40	7x19	6,400	110	C & M		
9/32	7.10	7x19	7,800	139	С		
5/16	7.90	7x19	9,000	173	C & M		
3/8	9.50	7x19	12,000	243	C & M		