

Commercial & Mil-Spec Strand- Galvanized Carbon Steel

1x7 Preformed Galvanized Steel Strand Non-Flexible

Diameter (inches)	Diameter (Metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/ 1000 ft.	Code
1/32	0.8	1x7	185	2.5	C
3/64	1.20	1x7	375	5.5	C
1/16	1.60	1x7	500	8.5	C
5/64	2.00	1x7	800	14	C
3/32	2.40	1x7	1200	27	C
1/8	3.20	1x7	2,100	35	C

1X19 Preformed Galvanized Steel Strand Non-Flexible

Diameter (inches)	Diameter (Metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/ 1000 ft.	Code
3/64	1.20	1x19	375	5.5	C
1/16	1.60	1x19	500	8.5	C
5/64	2.00	1x19	800	14	C
3/32	2.40	1x19	1,200	20	C & M
7/64	2.80	1x19	1,600	35	C
1/8	3.20	1x19	2,100	35	C
5/32	4.00	1x19	3,300	55	C
3/16	4.80	1x19	4,700	77	C
7/32	5.60	1x19	6,300	102	C
1/4	6.40	1x19	8,200	135	C
5/16	7.90	1x19	12,500	210	C