

COMMERCIAL & MIL-SPEC STRAND- STAINLESS

1X7 Preformed T302/04 Stainless Steel Strand Non-Flexible

Diameter (inches)	Diameter (Metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/ 1000 ft.	Code
1/64	0.40	1X7	40	0.53	C
1/32	0.80	1X7	185	2.5	C
3/64	1.20	1X7	375	5.5	C
1/16	1.60	1X7	500	8.5	C
5/64	2.00	1X7	800	14	C
3/32	2.40	1X7	1,200	20	C
7/64	2.80	1X7	1,600	27	C
1/8	3.20	1X7	2,100	35	C
5/32	4.00	1X7	3,300	55	C
3/16	4.80	1X7	4,700	73	C
1/4	6.40	1x7	8,500	135	C
5/16	7.90	1x7	13,200	212	C
3/8	9.50	1x7	18,000	300	C

1X19 Preformed T302/04 Stainless Steel Strand Non-Flexible

Diameter (inches)	Diameter (Metric)	Construction	Min. Break Strength (lbs.)	Approx. Mass Wt(lbs.)/ 1000 ft.	Code
3/64	1.20	1X19	375	5.5	C
1/16	1.60	1X19	500	8.5	C & M
5/64	2.00	1X19	800	14	C
3/32	2.40	1X19	1,200	20	C
7/64	2.80	1X19	1,600	27	C
1/8	3.20	1X19	2,100	35	C
5/32	4.00	1X19	3,300	55	C & M
3/16	4.80	1X19	4,700	77	C
7/32	5.60	1X19	6,300	102	C
1/4	6.40	1X19	8,200	135	C